302' Duel Fuel Class DPS-2 PSV DWT 5,312

HARVEY ENERGY



DIMENSIONS & DOCUMENTATIONS

Length Overall: 302 ft 92.1 m 64 ft 19.5 m ft 7.77 m Beam: Depth: GRT (ITC): <6,000 Net: Max Draft: 19.92 ft 6.07 m Classification: ABS US Min Draft: 11.50 ft 3.51 m Flag: Classification ID: **TBD** O.N. **TBD** Year Built: 2014

IMO: TBD

Notations: †A1, Offshore Support Vessel, †AMS, †ACCU, †DPS-2, ENVIRO+, GP, UWILD, FFV-1,

GFS(Dual Fuel Diesel), Circle E

Certifications Subchapter I, Subchapter L, SOLAS

PERFORMANCE

Maximum Speed:	14.00 knots	Fuel Consumption:	284 gal/hr	1,074.7 l/hr
Cruising Speed:	12.00 knots	Fuel Consumption:	186 gal/hr	703.8 l/hr
Maximum Speed:	14.00 knots	LNG Consumption:	393 gal/hr	1,487.1 l/hr
Cruising Speed:	12.00 knots	LNG Consumption:	185 gal/hr	700.0 l/hr
		LNG Capacity:	78,000 USG	295.3 m^3

MACHINERY

Main Generators: 3 x Wartsila 6L34DF Total Rating: 7,530 kW Main Propulsion: 2 x Wartsila FS300-S/WN Total Horsepower: 7,241 HP

Azimuthing Propellors in Nozzle

Bow Thrusters: 2 x Wartsila Total Horsepower: 1,992 BHP

Power Generation: 690V/60Hz/3Phase

CAPACITIES & DISCHARGE RATES

CITITION	T DISCILLING I	TI I I I I				
Deadweight:	5,312 Lt (.est)	5,398.8 Mt	Cargo Deck Area:	190.5 ft x	55.0 ft	10,480 ft ²
Deck Cargo:	4,500 Lt (.est)	4,573.5 Mt		58.1 m x	16.8 m	974.1 m ²
Deck Strength:	1,000 lbs/ft ²	5 t/m^2				
Drill/Rig Water:	621,237 USG	$2,351.6 \text{ m}^3$	Discharge Rate:	750 GPM	170.3	m ³ /hr
Liquid Mud:	18,000 bbls	$2,861.8 \text{ m}^3$	Discharge Rate:	1,000 Bbl/hr	159.0	m ³ /hr
Fuel:	253,194 USG	958.4 m^3	Discharge Rate:	750 GPM	170.3	m ³ /hr
Methanol:	1,613 bbls	256.4 m^3	Discharge Rate:	250 GPM	56.8	m ³ /hr
Dry Bulk:	$10,250 \text{ ft}^3$	290.2 m^3	Discharge Rate:	80 psi	6 bar	
Potable Water:	16,730 USG	63.3 m^3		-		

Fire Monitor: 2 x 5,284 GPM 1,200.1 m³/hr

ELECTRONICS

Kongsberg K-Pos 21Green DP, 3 X Kongsberg SeatexDGPS Systems, 3 X C. Plath Navigat XMk1,Mod, 10, 1 X Cyscan Laser: 1 X RADius 1000Triple: 3 XDGPS Inputs, Kongsberg C-Joy, (2) Furuno FAR2137-12 S band / Furuno FAR2117 X band, Furuno FE700, Furuno DS-80, Furuno RC1800T, Furuno FS-2571-C / Furuno FS-1503, Furuno FELCOM15STD-C, Furuno FNX-700P, Furuno IC-307

ACCOMMODATIONS

19 air conditioned/heated staterooms for 42 person(s) berthing total. The rooms are configured as follows:

2 air conditioned staterooms for 1 person(s) berthing each. 14 air conditioned staterooms for 2 person(s) berthing each.

3 air conditioned staterooms for 4 person(s) berthing each.

1 x Lounge, 1 x Conference/Internet Room

SPECIAL FEATURES

Liferafts: 4 X 25 Man USCG and SOLAS Approved DPS Hydro-Acoustic Well

Fast Rescue Craft: 1 Shart Harding with 40 hp Motor Computerized Tank Level Indicator System

Foam Capability: 30 minutes of foam capability Incinerator, Water Maker

Stores Crane: 1 x Green Marine Telescoping Max Lift @ Max Radius: 1,500 Lbs @ 27 ft 680.4 kg @ 8.2 m

NOTICE: The information contained herein is provided solely for the convenience of reference, and Harvey Gulf International Marine does not warrant the accuracy or completeness of the data listed above, which may vary from the current condition of the vessel or equipment. Harvey Gulf International Marine accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.

rements boundariouslf come	
www.harvevgult.com	