




250' Class DPS-2 PSV DWT 3,080

HARVEY ROVER



DIMENSIONS & DOCUMENTATIONS

Length Overall:	250 ft	76.2 m	Beam:	56 ft	17.1 m	Depth:	18.0 ft	5.49 m
GRT (ITC):	1,786		Net:	701		Max Draft:	14.46 ft	4.41 m
Classification:	ABS		Flag:	US		Min Draft:	7.50 ft	2.29 m
Classification ID:	10204057		O.N.	1218416		Year Built:	2011	
IMO:	9536259							
Notations:	ABS †A1, †AMS, †DPS 2, Circle E							
Certifications	Subchapter L, SOLAS							

PERFORMANCE

Maximum Speed:	12.00 knots	Fuel Consumption:	164 gal/hr	622.0 l/hr
Cruising Speed:	10.00 knots	Fuel Consumption:	147 gal/hr	556.6 l/hr

MACHINERY

Main Engines:	2 x Cummins QSK60	Total Horsepower:	4,000 BHP
Propellers:	FPP, 4 Blade	Propeller Diameter:	81 in 2,057 mm
Main Generators:	3 x Cummins QSM11-DM	Total Rating:	900 kW
Bow Thrusters:	2 x CPP Schottel	Total Horsepower:	1,500 BHP
Stern Thruster:	1 x FPP Schottel	Total Horsepower:	350 BHP
Rudders:	Independent Steering, Becker, High-Lift	Power Generation:	480V/60Hz/3Phase

CAPACITIES & DISCHARGE RATES

Deadweight:	3,080 Lt	3,130.3 Mt	Cargo Deck Area:	175.0 ft x 47.0 ft	8,225 ft ²
Deck Cargo:	2,119 Lt	2,153.6 Mt		53.4 m x 14.3 m	764.5 m ²
Deck Strength:	540 lbs/ft ²	2.6 t/m ²			
Drill/Rig Water:	260,125 USG	984.7 m ³	Discharge Rate:	525 GPM	119.2 m ³ /hr
Liquid Mud:	9,331 Bbls	1,483.5 m ³	Discharge Rate:	700 Bbl/hr	111.3 m ³ /hr
Fuel:	165,318 USG	625.8 m ³	Discharge Rate:	425 GPM	96.5 m ³ /hr
Dry Bulk:	6,000 ft ³	169.9 m ³	Discharge Rate:	80 psi	6 bar
Potable Water:	26,600 USG	100.7 m ³			

Fire Monitor: 1 x 1,900 GPM 431.5 m³/hr

ELECTRONICS

(ABS DPS 2)Beier Radio IVCS 2002, Furuno FE-700, Sentinel, AMEX-420 R4 NAV CENTER, CYSCAN, RADISCAN, CNAV 1000, Bier Radio IVCS 2002, 3 x Yokogawa CM29008, REFLECT A1, Sentinel, Furuno 0560 A3, Furuno IB583, Furuno NX-700, 2 X Furuno MU201CR, Furuno RC 1825A-3, Sentinel, Bogden GS 250, ICOM M504

ACCOMMODATIONS

8 air conditioned/heated staterooms for 22 person(s) berthing total. The rooms are configured as follows:
2 air conditioned staterooms for 1 person(s) berthing each. 3 air conditioned staterooms for 2 person(s) berthing each.
2 air conditioned staterooms for 4 person(s) berthing each. 1 air conditioned staterooms for 6 person(s) berthing each.

SPECIAL FEATURES

Anchore Windlass:	Electro Hydraulic	Rescue Boat:	Fassmer RR 4.2
CO ² Fixed System:	Kidd Finwall	EPIRB:	ACR 2406
Fuel Oil Meter W/ Printer:	Smith Meter	SARTS:	ACR Pathfinder 3
Life Rafts:	Four 25 Man Inflatable Liferrafts		
Deck Crane:	DMW Marine Telescoping Crane	Maximum Lift:	7.3 Lt @ 15.6 ft 7.4 Mt @ 4.75 m
		Minimum Lift:	4.1 Lt @ 27.7 ft 4.2 Mt @ 8.45 m

NOTICE: The information contained herein is provided solely for the convenience of reference, and Harvey Gulf International Marine does not warrant the accuracy or completeness of the data listed above, which may vary from the current condition of the vessel or equipment. Harvey Gulf International Marine accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.

www.harveygulf.com

CORPORATE OFFICE: 701 Poydras St., Suite 3700, New Orleans, LA 70139 Phone: 504.348.2466 Fax: 504.348.8060
HOUSTON OFFICE: 1990 Post Oak Blvd., Bldg 3 Suite 2400 Houston, Texas 77056 Fax: 713.877.1434
OPERATIONS OFFICE: 18399 East Main St., Galliano, LA 70354 Phone: 985.475.6631 Fax: 985.475.6507
ALASKA OFFICE: 3601 C St., Suite 1378, Anchorage, AK 99503 Phone: 504.348.2466 Fax: 504.348.8060