



280' Class DPS-2 PSV DWT 3,629

HARVEY SPIRIT



DIMENSIONS & DOCUMENTATIONS

Length Overall:	280 ft	85.4 m	Beam:	60 ft	18.3 m	Depth:	19.50 ft	5.95 m
GRT (ITC):	2,261		Net:	807		Max Draft:	15.90 ft	4.85 m
Classification:	ABS		Flag:	US		Min Draft:	9.60 ft	2.93 m
Classification ID:	7165265		O.N.	1191230		Year Built:	2009	
IMO:	9388106							
Notations:	ABS †A1, †AMS, †DPS 2, Circle E							
Certifications	Subchapter L, SOLAS							

PERFORMANCE

Maximum Speed:	13.00 knots	Fuel Consumption:	275 gal/hr	1040.6 l/hr
Cruising Speed:	10.00 knots	Fuel Consumption:	150 gal/hr	567.6 l/hr

MACHINERY

Main Engines:	GE 7FDM12 X 2	Total Horsepower:	6,140 BHP
Propellers:	2 Fixed Pitch 5 Blade	Propeller Diameter:	96 in 2,438 mm
Main Generators:	Cummins KTA19	Total Rating:	1,275 kW
Bow Thrusters:	2 Cummins KTA 32 Controll Pitch	Total Horsepower:	2,200 BHP
Stern Thruster:	1 Cummins KTA 32 Controll Pitch	Total Horsepower:	1,100 BHP
Rudders:	Schilling Fishtail; Independent Steering	Power Generation:	480V/60Hz/3Phase

CAPACITIES & DISCHARGE RATES

Deadweight	3,629 Lt	3,688.3 Mt	Cargo Deck Area:	202.0 ft x 52.0 ft	10,504 ft ²
Deck Cargo:	2,670 Lt	2,713.6 Mt		61.6 m x 15.9 m	975.0 m ²
Deck Strength:	1,050 lbs/ft ²	5.1 t/m ²	Discharge Rate:	800 GPM	181.7 m ³ /hr
Drill/Rig Water:	344,257 USG	1,303.2 m ³	Discharge Rate:	750 Bbl/hr	170.3 m ³ /hr
Liquid Mud:	10,580 Bbls	1,682.1 m ³	Discharge Rate:	700 GPM	159.0 m ³ /hr
Methanol:	60,592 USG	229.3 m ³	Discharge Rate:	800 GPM	181.7 m ³ /hr
Fuel:	154,437 USG	584.6 m ³	Discharge Rate:	80 psi	6 bar
Dry Bulk:	12,355 ft ³	349.9 m ³			
Potable Water:	12,538 USG	47.5 m ³			

Fire Monitor: 2 x 2,500 GPM 567.8 m³/hr

ELECTRONICS

Kongsberg Simrad SPD 22, Furuno GPS Navigator 150 / Seatex DPS 116, 3 X Sperry Navigat X MK 1, 1 X MK 4.2 2000 Meter Fanbeam / 3 X RADIUS 1000-S with 2 X 700 transponders, 2 X Kongsberg Simrad C-JOY OT, 10" "Baker Lyman", 2 X Furuno FAR-2117 Series, Furuno FE700, Furuno Felcom 15, Furuno SEA 235, Furuno Felcom 15, Furuno NX 700, Furuno FS 2570, Wave Call 3000, Global Synergies

ACCOMMODATIONS

- 8 air conditioned/heated staterooms for 20 person(s) berthing total. The rooms are configured as follows:
- 2 air conditioned staterooms for 1 person(s) berthing each. 3 air conditioned staterooms for 2 person(s) berthing each.
- 3 air conditioned stateroom 4 person(s) berthing each.
- 1 x Lounge

SPECIAL FEATURES

Windlass:	Coastal Machinery 2W15031-13	Anchor / Chain:	2 X 4,630 lb. Danforth / 1.5" X 720'
Liferafts:	4 X 20 Man USCG and SOLAS Approved	Computerized Cargo Discharge System	
Rescue Craft:	1 MK 2 6 Meter Fiberglass Hull W/50 Hp Tohatsu Motor	Fuel Management Program	
Computerized Tank Level Indicator System		Ergonomically Designed Pilothouse	
Computerized Vessel Stability Program		Computerized Navigation Map Program	
Liquid Mud Pipe Stripping System			

NOTICE: The information contained herein is provided solely for the convenience of reference, and Harvey Gulf International Marine does not warrant the accuracy or completeness of the data listed above, which may vary from the current condition of the vessel or equipment. Harvey Gulf International Marine accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.

www.harveygulf.com