



DP-2 SOLAS Multi-Purpose Field Support Vessel

HARVEY STONE



DIMENSIONS & DOCUMENTATIONS

Length Overall:	220 ft	67.1 m	Beam:	59 ft	18.0 m	Depth:	25.7 ft	7.835 m
GRT (ITC):	2,343		Net:	702		Max Draft:	21 ft 9'	6.40 m
Classification:	ABS		Flag:	US		Min Draft:	16 ft	4.88 m
Classification ID:			O.N.	1257725		Year Built:	2016	
IMO:	9752577							
Certifications	ABS, SOLAS, Sub-chapter I and L							
Notations:	ABS + A1, AHTS (DSV capable, ROV capable, AH, TOW Supply) +AMS, + ACCU, ACP, UWILD, FFV-2, + Circle E, HAB+(WB), ENVIRO							

PERFORMANCE

Maximum Speed:	14 knots	Fuel Consumption:	250 gal/hr	946.0 l/hr
Cruising Speed:	10 knots	Fuel Consumption:	208 gal/hr	787.1 l/hr

MACHINERY

Main Engines:	2 x GE IMO TIER 4	Total Horsepower:	10,000 BHP
Propellers:	2 X Schottel CPP Z-Drive	Propeller Diameter:	134 in 3,399 mm
Main Generators:	2 x Cummins QSK19DM	Total Rating:	1000 kW
Shaft Generators:	2 x Marellis	Total Rating:	2000 kW
Emergency Generators:	1 x Cummins UCM274F	Total Rating:	120 kW
Bow Thrusters:	2 x STT Schottel	Total Horsepower:	1,609 BHP

TOWING / ANCHOR HANDLING

Towing Winch	1 x MacGregor Hydraulic Winch, Double Drum Waterfall		
Stern Roller	200 t	Main Drum Capacity	1500m x 76 mm dia (SWR)
Tugger Winch	2 x 10t	2nd Drum Capacity	2,700 ft x 3 in.
Capstans	2 x 5t	Bow winch	900 ft of Synthetic Rope
Bollard Pull FWD	121 Short Tons	Bollard Pull Astern	68 short tons

CAPACITIES & DISCHARGE RATES

Deadweight:	1,280 Lt	1,300.9 Mt	Usable Deck Area:	25.0 ft x 45.0 ft	1,125 ft ²
Deck Cargo:	246 Lt	250.0 Mt		7.6 m x 13.7 m	104.6 m ²
Deck Strength:	1,024 lbs/ft ²	5.0 t/m ²			
Drill/Rig Water:	351,877 USG	1,332.0 m ³	Discharge Rate:	400 GPM	90.8 m ³ /hr
Fuel:	228,509 USG	865.0 m ³	Discharge Rate:	400 GPM	90.8 m ³ /hr
Potable Water:	47,287 USG	179.0 m ³	Range:	10,000 NM @ 10 Knots	
Fire Fighting:	FiFi 2	2 Monitors	Discharge rate each monitor @	2,642 GPM	600.1 m ³ /hr

ELECTRONICS

(ABS DPS 2)Beier Radio IVCS 4000-IJ, CyScan, Furuno FAR 2117BB, Furuno GP 150D, Mk200s, Furuno FE 700, Furuno FA 150 AIS, Furuno NX700P, Furuno RC1815 A3, Furuno FMD 3200 ECDIS, 1 x EIRB, 2 x SART, 3 x ICOM GM 1600, Furuno BR 500, VHF,

ACCOMMODATIONS

- 15 air conditioned/heated staterooms for 24 person(s) berthing total. The rooms are configured as follows:
- 6 air conditioned staterooms for 1 person(s) berthing each.
- 9 air conditioned staterooms for 2 person(s) berthing each.
- 1 Medical

SPECIAL FEATURES

Anchore Windlass:	Electro Hydraulic	Rescue Boat:	SOLAS (FRC) (15) person
CO ² Fixed System:		EPIRB:	1 x Safesea ERIPB
Fuel Oil Meter W/ Printer:		SARTS:	2 x Safesea SART
Life Rafts:	(6) 12 Man Inflatable Liferafts		
Deck Crane:	Crane Wire Length 45m	Maximum Lift:	10.0 Lt @ 39.4 ft 10.2 Mt @ 12 m
		Minimum Lift:	4.1 Lt @ 27.7 ft 4.2 Mt @ 8.45 m

EPP certified for 120 persons. Vessel is equipped with a survival room consisting of 120 seats for survival passengers

NOTICE: The information contained herein is provided solely for the convenience of reference, and Harvey Gulf International Marine does not warrant the accuracy or completeness of the data listed above, which may vary from the current condition of the vessel or equipment. Harvey Gulf International Marine accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.

www.harveygulf.com